



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
<b>HS401 GENERAL LEARNING UNIT</b>					
HS401.01	General Learning Space - Adjoining	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER Allow for hanging displays and medium impact resistance.
HS401.02	General Learning Space with Independent Learning Area	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER Allow for hanging displays and medium impact resistance.
HS401.07	General Learning Space - Divisible	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER Allow for hanging displays and medium impact resistance.
HS401.03	Shared Learning Space with Practical Activities Area	-	-	PINBOARD FINISH Maximise pinboard finish from 900 to 2100mm Co-ordinate with ducting	-
HS401.04	Seminar Room- General	-	-	-	-
HS401.05	GLS Store Room	-	-	-	-
HS401.06	Practical Activities Area	-	-	SPLASHBACK 450mm high Splashback to Sink Bench	-
<b>HS402 SENIOR LEARNING UNIT</b>					
HS402.01	Shared Study Space with Practical Activities Area	-	-	PINBOARD FINISH Maximise pinboard finish from 900 to 2100mm Co-ordinate with ducting	-
HS403.01	Senior Learning Centre with Practical Activities Area	-	-	PINBOARD FINISH Maximise pinboard finish from 900 to 2100mm Co-ordinate with ducting	-
<b>HS404 SCIENCE LEARNING UNIT</b>					
HS404.01	Science General Learning Space with Demonstration Bench	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor. 450mm high splashback to bench with	-
HS404.10	Small Science General Learning Space	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS404.02	Shared Science Laboratory	-	-	PINBOARD FINISH Maximise pinboard finish from 900mm to 2100mm to front and rear wall. 450mm high splashback above benches and sinks (except where glazing is within the zone)	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS404.03	Seminar Room - Lab/Workshop	-	-	-	-
HS404.04	Science Preparation	-	-	SPLASHBACK 450mm high Splashback for Sinks and Benches (excluding when glazing is within that zone). Splashback to extend higher behind wall mounted Draining Racks.	-
HS404.06	Apparatus Store Room	-	-	-	-
HS404.07	Apparatus Storage	-	-	-	-
HS404.08	Chemical Store Room	-	FIRE RATED WALL - Fire rated walls required (~60/60)	-	WALL - OTHER Fire Rated Walls (FRL 120/120/120) Corrosion Resistant masonry walls to acid bay.
HS404.09	Botany/Zoology Room	-	-	SPLASHBACK 450mm high Splashback for Bucket Sinks and Plant Soaking Shelf.	-
<b>HS405 VISUAL ARTS LEARNING UNIT</b>					
HS405.01	Visual Arts General Learning Space	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS405.02	Visual Arts Learning Space with Art Trough	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall when Operable wall not installed. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER 450mm high Stainless Steel splashback to Laundry trough and bench with art trough.
HS405.03	Shared Visual Arts Workshop	-	-	PINBOARD FINISH Maximise pinboard finish from 900mm to Ceiling.	WALL - OTHER 450mm high Stainless Steel Splashback to Art trough bench and laundry tub, or to underside of window sill when present.
HS405.04	Visual Arts Store Room	-	-	-	-
HS405.05	Visual Arts Project Store Room	-	-	-	-
HS405.06	Dark Room	-	-	-	WALL - OTHER 450mm high splashback to sinks and benches. Light Trap painted matt black.
HS413.01	Materials Workshop	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise Cork/Linoleum pinboard finish from 900mm or top of splashback to ceiling,	WALL - OTHER Walls to be durable and easy to clean 450mm high Stainless Steel Splashback to Art Trough, Laundry Tub and Basin. Splashback to extend to sill height when glazing above.



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS413.02	Project Store Room	-	-	-	-
<b>HS407 PERFORMANCE &amp; FITNESS LEARNING UNIT</b>					
HS406.01	Shared Health/PE & Performing Arts Workshop	-	-	-	-
HS406.02	Performing Arts Store Room	-	-	-	-
HS406.03	Seminar Room - Practice	-	-	PINBOARD FINISH Maximise pinboard finish from 900mm to 2100mm.	-
HS407.02	PE & Fitness Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	-
HS407.04	General Learning Space - With Performance Area	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2100mm to front and rear wall when Operable wall not installed. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS408.01	Shared PE Fitness Laboratory with Wet Area	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from 900mm to Ceiling.	-
HS408.03	Change Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Easy Clean and Water resistant surfaces
<b>HS409 TAS MAT 1 - KITCHEN</b>					
HS409.01	Food & Textile Technology General Learning Space with Kitchen Demonstration Bench	-	-	PINBOARD FINISH Maximise pinboard finish from floor to ceiling to front and rear walls. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS409.02	Food & Textile Technology General Learning Space with Sink	-	-	PINBOARD FINISH Maximise pinboard finish from floor to ceiling to front and rear walls. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER 450mm high Splashback to sinks and adjoining benches, except when window is within the zone.
HS409.03	Shared Domestic Kitchen	-	-	PINBOARD FINISH Maximise Cork/Linoleum pinboard finish from 900mm or top of splashback to 2100mm.	WALL - OTHER 450mm high Splashback to sinks, adjoining benches and basins, except when window is within the zone.
HS414.01	Semi-Commercial Kitchen	-	-	PINBOARD FINISH Maximise Cork/Linoleum pinboard finish from 900mm or top of splashback to 2100mm.	WALL - OTHER 450mm high Splashback to sinks, adjoining benches and basins, except when window is within the zone.



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS409.04	Kitchen - Store Room	-	-	-	-
HS409.05	Kitchen - Preparation	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Rendered and painted walls for durability and easy cleaning. 450mm high Splashback to sinks, adjoining benches and basins, except when window is within the zone.
HS409.07	Pantry - Domestic	-	-	-	-
HS414.02	Pantry - Semi-Commercial	-	-	-	-
HS409.08	Laundry	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER 450mm high Splashback to sinks, adjoining benches and basins, except when window is within the zone.
<b>HS410 TAS MAT 2 - WOOD &amp; METAL</b>					
HS410.01	Wood & Metal Technology General Learning Space - With Sink	-	-	PINBOARD FINISH Maximise pinboard finish from floor to ceiling to front and rear walls. Pinboard not required below windows with sills less than 1800mm above floor.	WALL - OTHER 450mm high Splashback to sinks.
HS410.02	Wood & Metal Technology General Learning Space	-	-	PINBOARD FINISH Maximise pinboard finish from floor to ceiling to front and rear walls. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS410.03	Shared Wood & Metal Workshop	-	-	PINBOARD FINISH Maximise Cork/Linoleum pinboard finish from 900mm or top of splashback to 2100mm, but not in Finishing area or Welding/Hot Metals Area.	WALL - OTHER 450mm high Stainless Steel Splashback to bucket sink.
HS410.04	Wood & Metal Materials Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	-
HS410.05	Wood & Metal Project Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Internal Chain wire mesh dividing wall and sliding gate
HS410.06	Materials Learning Space - Wood & Metal	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise Cork/Linoleum pinboard finish from 900mm to 2100mm,	WALL - OTHER Wall finishes to be appropriate to the industrial type environment



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
<b>HS411 MULTIMEDIA LEARNING UNIT</b>					
HS411.01	Shared Multimedia Workshop	-	-	PINBOARD FINISH Maximise pinboard finish from floor to ceiling to front and rear walls. Pinboard not required below windows with sills less than 1800mm above floor.	-
HS411.02	Multimedia Store Room	-	-	-	-
HS411.03	Multimedia Studio	-	-	-	-
<b>HS412 LECTURE LEARNING UNIT</b>					
HS412.01	Lecture Theatre	-	-	-	-
HS412.02	Lecture Store Room	-	-	-	-
<b>HS430 SPECIAL EDUCATION LEARNING UNIT (IO/IS/P)</b>					
HS430.01	General Learning Space - IO	-	-	-	-
HS430.02	General Learning Space - IS/P	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	WALL - OTHER Allow for Hanging Displays
HS430.10	Shared Practical Activities Area - IO/IS/P	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	WALL - OTHER Allow for Hanging Displays 300mm Splashback to benches (NOT P.E.S)
HS430.20	GLS Store Room - IO/IS/P	-	-	-	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
<b>HS440 SPECIAL EDUCATION LEARNING UNIT (BD/CD/ED)</b>					
HS440.01	General Learning Space - BD/CD/ED	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	-
HS440.10	Multipurpose Space - BD/CD/ED	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	WALL - OTHER Allow for Hanging Displays
HS440.20	Project Store Room - BD/CD/ED	-	-	-	-
<b>HS450 SPECIAL EDUCATION LEARNING UNIT (TUTORIAL)</b>					
HS450.01	Independent Learning Space - Tutorial	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	WALL - OTHER Allow for Hanging Displays
HS450.02	Tutorial Centre Seminar Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Maximise pinboard finish from floor to 2.1m.	-
<b>HS501 LIBRARY</b>					
HS501.01	Library Main Entry	-	-	-	WALL - OTHER Maximise display potential at high level
HS501.03	Library Main Area	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 3m, including behind fixed wall shelving.	-
HS501.07	Printing/Photocopying Area	-	-	PINBOARD FINISH Maximise pinboard finish from floor to 3m, including behind fixed wall shelving.	-
HS501.08	Seminar Room - Divisible	-	-	-	-
HS501.09	Library Administration	-	-	-	WALL - OTHER 450mm high Splashback to sinks.
HS501.13	Computer Learning Space	-	-	PINBOARD FINISH Maximise pinboard finish from 1000mm to 2100mm.	-
HS501.14	Computer Store Room	-	-	-	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS501.15	Senior Study	-	-	-	-
HS501.17	Careers Adviser's Office	-	-	-	-
HS501.18	System Administrator's Office	-	-	-	-
HS501.19	Communications Room	-	-	-	-
<b>HS502 MOVEMENT COMPLEX</b>					
HS502.01	Gymnasium	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Fire Rated Pin Board 6m long x 1.2m high starting at 0.9m	WALL - OTHER Impact Resistant wall to 2.1m (possibly netting in front of low cost wall)
HS502.03	Gymnasium - Extension	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Fire Rated Pin Board 6m long x 1.2m high starting at 0.9m	WALL - OTHER Impact Resistant wall to 2.1m (possibly netting in front of low cost wall)
HS502.18	Gymnasium - Half Court	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Fire Rated Pin Board 3m long x 1.2m high starting at 0.9m	WALL - OTHER Impact Resistant wall to 2.1m (possibly netting in front of low cost wall)
HS502.04	Movement Studio	IMPACT RESISTANCE Impact resistant walls are recommended	-	PINBOARD FINISH Fire Rated Pin Board 6m long x 1.2m high starting at 0.9m	WALL - OTHER Acoustic Treatment required. Impact Resistant wall in dark colour painted or prefinished lining. Minimum wall opposite floor area
HS502.05	Sports Equipment Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~-/60/60)		WALL - OTHER Fire Rated walls to stores in Entertainment Venues
HS502.06	Large Equipment Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~-/60/60)		WALL - OTHER Fire Rated walls to stores in Entertainment Venues
HS502.07	Outdoor Equipment Store Room	-	-	-	-
HS502.08	Chair Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~-/60/60)		WALL - OTHER Fire Rated walls to stores in Entertainment Venues
HS502.10	Movement Studio Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~-/60/60)		WALL - OTHER Fire Rated walls to stores in Entertainment Venues
HS502.11	Control Room	-	-	-	-
HS502.12	First Aid	-	-	-	WALL - OTHER 450MM HIGH SPLASHBACK TO Sink and Bench
HS502.13	Shower	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Walls to be impact resistant and easy clean, with Ceramic tiles to 1.8m above floor in shower areas



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS502.15	Staff Shower	-	-	-	WALL - OTHER Walls to be impact resistant and easy clean, with Ceramic tiles to 1.8m above floor in shower areas
HS502.16	Stage	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Impact Resistant wall to 2.1m (possibly netting in front of low cost wall)
HS502.17	Demountable Platform	-	-	-	-
<b>HS503 OUTDOOR COVERED WORKSHOP</b>					
HS503.01	Shared Outdoor Covered Workshop	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Walls to be impact resistant and robust Stainless Steel Splashback to Bucket Sink.
HS503.06	Outdoor Covered Workshop	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Walls to be impact resistant and robust
HS503.02	Welding/Hot Metals Area	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	-
HS503.03	Kiln Space	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~60/60)	-	WALL - OTHER Non-combustible wall lining.
HS503.04	LPG Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	FIRE RATED WALL - Fire rated walls required (~60/60)	-	WALL - OTHER Non-combustible wall lining.
HS503.05	Pottery Store Room	-	-	-	-
<b>HS504 OUTDOOR LEARNING</b>					
HS504.01	Outdoor Learning Space	-	-	-	-
HS504.02	Tiered Outdoor Learning Space	-	-	-	-
HS504.03	Outdoor Learning Space - Small Group	-	-	-	-
<b>HS505 GAMES</b>					
HS505.01	Games Court	-	-	-	WALL - OTHER Perimeter fence
HS505.03	Games Field	-	-	-	-





# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS505.04	Batting Practice Nets	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Batting practice safety fence to sides and rear of practice pitch Perimeter fence height minimum 3.4m. Lower fence edges maximum 150mm
<b>HS506 AGRICULTURE</b>					
HS506.01	Agriculture Shed Workshop	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	-
HS506.02	Agriculture Tools Storage	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	-
HS506.03	Animal Space	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Walls to be Pig and water resistant to 1m to enable hosing out etc.
HS506.04	Plant Space	-	-	-	WALL - OTHER Walls to be water resistant
HS506.05	Covered Area - Agriculture	-	-	-	WALL - OTHER Water resistant walls to 1m, Stainless Steel Splashback 300mm high to wash trough
HS506.06	Agriculture Plot	-	-	-	-
<b>HS601 ADMINISTRATION UNIT</b>					
HS601.01	Public Reception	-	-	-	WALL - OTHER Wall space for honour boards and displays
HS601.03	Student Reception	-	-	PINBOARD FINISH Maximise pinboard finish from 900mm to ceiling	WALL - OTHER Wall space for honour boards and displays
HS601.05	Student Waiting	-	-	-	-
HS601.06	Principal's Office / Meeting Room	-	-	-	-
HS601.07	Deputy Principal's Office	-	-	-	-
HS601.08	Interview Room / Office	-	-	-	-
HS601.09	Interview Room / Meeting	-	-	-	-
HS601.11	Administration - Clerical	-	-	-	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS601.14	Administration- Executive	-	-	-	-
HS601.17	Store Room	-	-	-	-
HS601.18	Clinic	-	-	-	WALL - OTHER 450mm high Splashback to Sink and Bench
HS601.21	Visitor's Office	-	-	-	-
HS601.22	Tea Room	-	-	-	WALL - OTHER 450mm high Splashback to Sink and Bench
HS601.23	Utility Space	-	-	-	-
HS601.81	Entrance Zone	-	-	-	-
<b>HS602 STAFF UNIT</b>					
HS602.01	Staff Study	-	-	-	-
HS602.04	Staff Lounge	-	-	-	WALL - OTHER 450mm high Splashback to Sink and Bench
HS602.08	Preparation/Printing	-	-	-	WALL - OTHER 450mm high Splashback to Sink and Bench
HS602.11	Staff Toilet	-	-	-	WALL - OTHER 450mm high Splashback to Sink and Bench
HS602.12	Access Shower/Toilet	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Brickwork walls with ceramic tiles to door head height
<b>HS603 STUDENT SERVICES UNIT</b>					
HS603.01	Toilets	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Water resistant, easy-clean walls. 300mm high Stainless steel splashback to wash trough
HS603.02	Drinking Facilities	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Water resistant, easy-clean walls. 300mm high Stainless steel splashback to wash trough
HS603.03	Seating	-	-	-	-
HS603.04	Hand Washing Outlets	-	-	-	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS603.06	Access Shower/Toilet/Change	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Brickwork walls with ceramic tiles to minimum 1.5m height and 2.1m in shower area.
HS603.09	Laundry	-	-	-	WALL - OTHER easy clean water resistant walls Splashback to Laundry Tub
<b>HS604 CANTEEN</b>					
HS604.01	Canteen	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Rendered and painted masonry walls. 450mm high splashback to Benches, Sinks and Basins
HS604.04	Canteen Office/Store Room	IMPACT RESISTANCE Impact resistant walls are recommended	-	-	WALL - OTHER Rendered and painted masonry walls.
HS604.07	Vending Machines	-	-	-	-
<b>HS605 STORAGE UNIT</b>					
HS605.01	Archive Store Room	-	-	-	WALL - OTHER Walls and ceiling to be sealed, room enclosure must provide dry storage
HS605.03	Garden Store Room	-	-	-	-
HS605.04	Bulk Store Room	-	-	-	-
HS605.05	Cleaning Supplies Store Room	-	-	-	-
HS605.06	Cleaning Distributed Store Room	-	-	-	WALL - OTHER 450mm high Stainless Steel Splashback to bucket sink
<b>HS606 COVERED OUTDOOR SPACE</b>					
HS606.01	Covered Outdoor Space	-	-	-	-
<b>HS607 ASSEMBLY COURT</b>					
HS607.01	Quadrangle	-	-	-	-
HS607.02	Flagpole	-	-	-	-
HS607.21	Assembly Zone	-	-	-	-
<b>HS608 PEDESTRIAN CIRCULATION</b>					
HS608.01	Paved Areas	-	-	-	-
HS608.02	Paved Access	-	-	-	-
<b>HS609 VEHICULAR CIRCULATION</b>					
HS609.01	Service Roads	-	-	-	-
HS609.04	Bulk Waste Pad	-	-	-	-



# Wall

## Schedule for Secondary School Rooms & Spaces

ID	ROOM/SPACE NAME	IR	FR	PF	OTH
HS609.05	Car Parking	-	-	-	-
HS609.06	Bus Zone	-	-	-	-
HS609.07	Bicycle Enclosure	-	-	-	-
HS609.08	Crossovers	-	-	-	-
<b>HS610 OPEN SPACES</b>					
HS610.01	Open Space	-	-	-	-
HS610.11	Street Frontage Zone	-	-	-	-
HS610.12	Active Zone	-	-	-	-
HS610.13	Passive Zone	-	-	-	-
HS610.14	Boundary Zone	-	-	-	-
HS610.15	Out of Bounds Zone	-	-	-	-
HS610.16	Special Function Zone	-	-	-	-
<b>HS611 SERVICES</b>					
HS611.01	Dust Extraction Space	-	FIRE RATED WALL - Fire rated walls required (--/60/60)		WALL - OTHER Non Combustible wall lining
HS610.17	Services Zone	-	-	-	-
HS611.02	Main Switchroom	-	-	-	-
HS611.03	Distribution Board Cupboard	-	-	-	-
<b>HS612 SITE</b>					
HS612.01	Fencing	-	-	-	-
HS612.03	Waste Recycling	-	-	-	WALL - OTHER Treated pine logs creating 3 compartments.
HS612.04	Signs	-	-	-	-
HS612.05	Site	-	-	-	-